

SPIRAX SARCO SIGMA 9Hazard Alert Code:
HIGH

Chemwatch Material Safety Data Sheet

Revision No: 3

Chemwatch 4925-46

Issue Date: 29-Jan-2010

CD 2010/1

Section 1 - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION**PRODUCT NAME**

Spirax Sarco Sigma 9

SYNONYMS

"filming amine"

PRODUCT USE

Filming amine for condensate systems.

SUPPLIER

Company: Spirax Sarco Pty Ltd

Address:

72 Mica Street

Carole Park


QLD, 4300

AUS

Telephone: +61 7 3879 4944

Telephone: +61 414 355 619 A/H

Fax: +61 7 3271 4589

HAZARD RATINGS**Section 2 - HAZARDS IDENTIFICATION****STATEMENT OF HAZARDOUS NATURE****HAZARDOUS SUBSTANCE. NON-DANGEROUS GOODS. According to NOHSC Criteria, and ADG Code.****POISONS SCHEDULE**

None

RISK

- Causes burns.
- Risk of serious damage to eyes.
- May cause SENSITISATION by skin contact.
- Toxic to aquatic organisms may cause long-term adverse effects in the aquatic environment.
- Inhalation may produce health damage*.
- Cumulative effects may result following exposure*.

* (limited evidence).

SAFETY

- Keep locked up.
- Do not breathe gas/ fumes/ vapour/ spray.
- Avoid contact with eyes.
- Wear suitable protective clothing.
- Use only in well ventilated areas.
- Keep container in a well ventilated place.
- To clean the floor and all objects contaminated by this material use water.
- Keep container tightly closed.
- This material and its container must be disposed of in a safe way.
- Take off immediately all contaminated clothing.
- In case of accident or if you feel unwell IMMEDIATELY contact Doctor or Poisons Information Centre (show label if possible).
- Use appropriate container to avoid environment contamination.
- Avoid release to the environment. Refer to special instructions/ safety data sheets.

Section 3 - COMPOSITION / INFORMATION ON INGREDIENTS

NAME	CAS RN	%
octadecylamine	124-30-1	1-10
water	7732-18-5	>60

NOTE: Manufacturer has supplied full ingredient information to allow CHEMWATCH assessment.

SPIRAX SARCO SIGMA 9

Hazard Alert Code:
HIGH

Chemwatch Material Safety Data Sheet

Revision No: 3

Chemwatch 4925-46

Issue Date: 29-Jan-2010

CD 2010/1

Section 4 - FIRST AID MEASURES

SWALLOWED

-
- For advice, contact a Poisons Information Centre or a doctor at once.
- Urgent hospital treatment is likely to be needed.
- If swallowed do NOT induce vomiting.
- If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration.
- Observe the patient carefully.
- Never give liquid to a person showing signs of being sleepy or with reduced awareness; i.e. becoming unconscious.
- Give water to rinse out mouth, then provide liquid slowly and as much as casualty can comfortably drink.
- Transport to hospital or doctor without delay.

EYE

- If this product comes in contact with the eyes:
 - Immediately hold eyelids apart and flush the eye continuously with running water.
 - Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids.
 - Continue flushing until advised to stop by the Poisons Information Centre or a doctor, or for at least 15 minutes.
 - Transport to hospital or doctor without delay.
 - Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.

SKIN

- If skin or hair contact occurs:
 - Immediately flush body and clothes with large amounts of water, using safety shower if available.
 - Quickly remove all contaminated clothing, including footwear.
 - Wash skin and hair with running water. Continue flushing with water until advised to stop by the Poisons Information Centre.
 - Transport to hospital, or doctor.

INHALED

-
- If fumes or combustion products are inhaled remove from contaminated area.
- Lay patient down. Keep warm and rested.
- Prostheses such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures.
- Apply artificial respiration if not breathing, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary.
- Transport to hospital, or doctor, without delay.

NOTES TO PHYSICIAN

- Treat symptomatically.

Section 5 - FIRE FIGHTING MEASURES

EXTINGUISHING MEDIA

-
- There is no restriction on the type of extinguisher which may be used.
- Use extinguishing media suitable for surrounding area.

FIRE FIGHTING

-
- Alert Fire Brigade and tell them location and nature of hazard.
- Wear breathing apparatus plus protective gloves for fire only.
- Prevent, by any means available, spillage from entering drains or water courses.
- Use fire fighting procedures suitable for surrounding area.
- DO NOT approach containers suspected to be hot.
- Cool fire exposed containers with water spray from a protected location.
- If safe to do so, remove containers from path of fire.
- Equipment should be thoroughly decontaminated after use.

FIRE/EXPLOSION HAZARD

-
- Non combustible.
- Not considered to be a significant fire risk.
- Expansion or decomposition on heating may lead to violent rupture of containers.
- Decomposes on heating and may produce toxic/ irritating fumes.
- May emit acrid smoke.

May emit corrosive fumes.

FIRE INCOMPATIBILITY

- None known.

HAZCHEM

None

Personal Protective Equipment

Gas tight chemical resistant suit.

Section 6 - ACCIDENTAL RELEASE MEASURES

SPIRAX SARCO SIGMA 9Hazard Alert Code:
HIGH

Chemwatch Material Safety Data Sheet

Revision No: 3

Chemwatch 4925-46

Issue Date: 29-Jan-2010

CD 2010/1

EMERGENCY PROCEDURES**MINOR SPILLS**

-
- Clean up all spills immediately.
- Avoid breathing vapours and contact with skin and eyes.
- Control personal contact by using protective equipment.
- Contain and absorb spill with sand, earth, inert material or vermiculite.
- Wipe up.
- Place in a suitable, labelled container for waste disposal.

MAJOR SPILLS

- Moderate hazard.
- Clear area of personnel and move upwind.
- Alert Fire Brigade and tell them location and nature of hazard.
- Wear breathing apparatus plus protective gloves.
- Prevent, by any means available, spillage from entering drains or water course.
- Stop leak if safe to do so.
- Contain spill with sand, earth or vermiculite.
- Collect recoverable product into labelled containers for recycling.
- Neutralise/decontaminate residue.
- Collect solid residues and seal in labelled drums for disposal.
- Wash area and prevent runoff into drains.
- After clean up operations, decontaminate and launder all protective clothing and equipment before storing and re-using.
- If contamination of drains or waterways occurs, advise emergency services.

Personal Protective Equipment advice is contained in Section 8 of the MSDS.

Section 7 - HANDLING AND STORAGE**PROCEDURE FOR HANDLING**

-
- Avoid all personal contact, including inhalation.
- Wear protective clothing when risk of exposure occurs.
- Use in a well-ventilated area.
- Avoid contact with moisture.
- Avoid contact with incompatible materials.
- When handling, DO NOT eat, drink or smoke.
- Keep containers securely sealed when not in use.
- Avoid physical damage to containers.
- Always wash hands with soap and water after handling.
- Work clothes should be laundered separately. Launder contaminated clothing before re-use.
- Use good occupational work practice.
- Observe manufacturer's storing and handling recommendations.
- Atmosphere should be regularly checked against established exposure standards to ensure safe working conditions are maintained.
- DO NOT allow clothing wet with material to stay in contact with skin

SUITABLE CONTAINER

-
- Polyethylene or polypropylene container.
- Packing as recommended by manufacturer.
- Check all containers are clearly labelled and free from leaks.

STORAGE INCOMPATIBILITY

-
- Avoid strong acids, acid chlorides, acid anhydrides and chloroformates.

STORAGE REQUIREMENTS

-
- Store in original containers.
- Keep containers securely sealed.
- Store in a cool, dry, well-ventilated area.
- Store away from incompatible materials and foodstuff containers.
- Protect containers against physical damage and check regularly for leaks.
- Observe manufacturer's storing and handling recommendations.

SAFE STORAGE WITH OTHER CLASSIFIED CHEMICALS

+

+

+

+

X

+

X: Must not be stored together

O: May be stored together with specific preventions

+: May be stored together

SPIRAX SARCO SIGMA 9Hazard Alert Code:
HIGH

Chemwatch Material Safety Data Sheet

Revision No: 3

Chemwatch 4925-46

Issue Date: 29-Jan-2010

CD 2010/1

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION**EXPOSURE CONTROLS**

The following materials had no OELs on our records

- octadecylamine: CAS:124-30-1
- water: CAS:7732-18-5

MATERIAL DATA

SPIRAX SARCO SIGMA 9:

Not available

OCTADECYLAMINE:

■ It is the goal of the ACGIH (and other Agencies) to recommend TLVs (or their equivalent) for all substances for which there is evidence of health effects at airborne concentrations encountered in the workplace.

At this time no TLV has been established, even though this material may produce adverse health effects (as evidenced in animal experiments or clinical experience). Airborne concentrations must be maintained as low as is practically possible and occupational exposure must be kept to a minimum.

NOTE: The ACGIH occupational exposure standard for Particles Not Otherwise Specified (P.N.O.S) does NOT apply.


Sensory irritants are chemicals that produce temporary and undesirable side-effects on the eyes, nose or throat. Historically occupational exposure standards for these irritants have been based on observation of workers' responses to various airborne concentrations. Present day expectations require that nearly every individual should be protected against even minor sensory irritation and exposure standards are established using uncertainty factors or safety factors of 5 to 10 or more. On occasion animal no-observable-effect-levels (NOEL) are used to determine these limits where human results are unavailable. An additional approach, typically used by the TLV committee (USA) in determining respiratory standards for this group of chemicals, has been to assign ceiling values (TLV C) to rapidly acting irritants and to assign short-term exposure limits (TLV STELs) when the weight of evidence from irritation, bioaccumulation and other endpoints combine to warrant such a limit. In contrast the MAK Commission (Germany) uses a five-category system based on intensive odour, local irritation, and elimination half-life. However this system is being replaced to be consistent with the European Union (EU) Scientific Committee for Occupational Exposure Limits (SCOEL); this is more closely allied to that of the USA.

OSHA (USA) concluded that exposure to sensory irritants can:

- cause inflammation
- cause increased susceptibility to other irritants and infectious agents
- lead to permanent injury or dysfunction
- permit greater absorption of hazardous substances and
- acclimate the worker to the irritant warning properties of these substances thus increasing the risk of overexposure.

WATER:

- No exposure limits set by NOHSC or ACGIH.

PERSONAL PROTECTION**EYE**

-
- Chemical goggles.
- Full face shield may be required for supplementary but never for primary protection of eyes
- Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lens or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in their removal and suitable equipment should be readily available. In the event of chemical exposure, begin eye irrigation immediately and remove contact lens as soon as practicable. Lens should be removed at the first signs of eye redness or irritation - lens should be removed in a clean environment only after workers have washed hands thoroughly. [CDC NIOSH Current Intelligence Bulletin 59]

HANDS/FEET

-
- Wear chemical protective gloves, eg. PVC.
- Wear safety footwear or safety gumboots, eg. Rubber
- When handling corrosive liquids, wear trousers or overalls outside of boots, to avoid spills entering boots.

NOTE:

- The material may produce skin sensitisation in predisposed individuals. Care must be taken, when removing gloves and other protective equipment, to avoid all possible skin contact.
- Contaminated leather items, such as shoes, belts and watch-bands should be removed and destroyed.

OTHER

-
- Overalls.
- P.V.C. apron.
- Barrier cream.
- Skin cleansing cream.
- Eye wash unit.

RESPIRATOR

■ Selection of the Class and Type of respirator will depend upon the level of breathing zone contaminant and the chemical nature of the contaminant. Protection Factors (defined as the ratio of contaminant outside and inside the mask) may also be important.

Breathing Zone Level ppm (volume)	Maximum Protection Factor	Half-face Respirator	Full-Face Respirator
1000	10	-AUS P	-
1000	50	-	-AUS P
5000	50	Airline *	-

SPIRAX SARCO SIGMA 9Hazard Alert Code:
HIGH

Chemwatch Material Safety Data Sheet

Revision No: 3

Chemwatch 4925-46

Issue Date: 29-Jan-2010

CD 2010/1

5000	100	-	-2 P
10000	100	-	-3 P
	100+		Airline**

* - Continuous Flow ** - Continuous-flow or positive pressure demand.

The local concentration of material, quantity and conditions of use determine the type of personal protective equipment required. For further information consult site specific CHEMWATCH data (if available), or your Occupational Health and Safety Advisor.

ENGINEERING CONTROLS

■ Local exhaust ventilation usually required. If risk of overexposure exists, wear approved respirator. Correct fit is essential to obtain adequate protection. Supplied-air type respirator may be required in special circumstances. Correct fit is essential to ensure adequate protection.

An approved self contained breathing apparatus (SCBA) may be required in some situations.

Provide adequate ventilation in warehouse or closed storage area. Air contaminants generated in the workplace possess varying "escape" velocities which, in turn, determine the "capture velocities" of fresh circulating air required to effectively remove the contaminant.

Type of Contaminant:	Air Speed:
solvent, vapours, degreasing etc., evaporating from tank (in still air).	0.25-0.5 m/s (50-100 f/min.)
aerosols, fumes from pouring operations, intermittent container filling, low speed conveyer transfers, welding, spray drift, plating acid fumes, pickling (released at low velocity into zone of active generation)	0.5-1 m/s (100-200 f/min.)
direct spray, spray painting in shallow booths, drum filling, conveyer loading, crusher dusts, gas discharge (active generation into zone of rapid air motion)	1-2.5 m/s (200-500 f/min.)
grinding, abrasive blasting, tumbling, high speed wheel generated dusts (released at high initial velocity into zone of very high rapid air motion).	2.5-10 m/s (500-2000 f/min.)

Within each range the appropriate value depends on:

Lower end of the range

- 1: Room air currents minimal or favourable to capture
- 2: Contaminants of low toxicity or of nuisance value only.
- 3: Intermittent, low production.
- 4: Large hood or large air mass in motion

Upper end of the range

- 1: Disturbing room air currents
- 2: Contaminants of high toxicity
- 3: High production, heavy use
- 4: Small hood-local control only

Simple theory shows that air velocity falls rapidly with distance away from the opening of a simple extraction pipe. Velocity generally decreases with the square of distance from the extraction point (in simple cases). Therefore the air speed at the extraction point should be adjusted, accordingly, after reference to distance from the contaminating source. The air velocity at the extraction fan, for example, should be a minimum of 1-2 m/s (200-400 f/min) for extraction of solvents generated in a tank 2 meters distant from the extraction point. Other mechanical considerations, producing performance deficits within the extraction apparatus, make it essential that theoretical air velocities are multiplied by factors of 10 or more when extraction systems are installed or used.

Section 9 - PHYSICAL AND CHEMICAL PROPERTIES**APPEARANCE**

White mildly alkaline liquid with an ammoniacal odour; dispersible in water.

PHYSICAL PROPERTIES

Liquid.

Mixes with water.

State	Liquid	Molecular Weight	Not applicable
Melting Range (°C)	0	Viscosity	Not available
Boiling Range (°C)	100	Solubility in water (g/L)	Miscible
Flash Point (°C)	Not applicable	pH (1% solution)	Not available
Decomposition Temp (°C)	Not available	pH (as supplied)	8-11
Autoignition Temp (°C)	Not applicable	Vapour Pressure (kPa)	Not available
Upper Explosive Limit (%)	Not applicable	Specific Gravity (water=1)	1.0-1.1
Lower Explosive Limit (%)	Not applicable	Relative Vapour Density (air=1)	Not available
Volatile Component (%vol)	Not available	Evaporation Rate	Not available

SPIRAX SARCO SIGMA 9

Hazard Alert Code:
HIGH

Chemwatch Material Safety Data Sheet

Revision No: 3

Chemwatch 4925-46

Issue Date: 29-Jan-2010

CD 2010/1

Section 10 - CHEMICAL STABILITY

CONDITIONS CONTRIBUTING TO INSTABILITY

-
- Presence of incompatible materials.
- Product is considered stable.
- Hazardous polymerisation will not occur.

For incompatible materials - refer to Section 7 - Handling and Storage.

Section 11 - TOXICOLOGICAL INFORMATION

POTENTIAL HEALTH EFFECTS

ACUTE HEALTH EFFECTS

SWALLOWED

- The material can produce chemical burns within the oral cavity and gastrointestinal tract following ingestion.

EYE

- The material can produce chemical burns to the eye following direct contact. Vapours or mists may be extremely irritating. If applied to the eyes, this material causes severe eye damage.

SKIN

- The material can produce chemical burns following direct contact with the skin.

INHALED

- Not normally a hazard due to non-volatile nature of product.

The material can cause respiratory irritation in some persons. The body's response to such irritation can cause further lung damage.

Inhalation of amine vapours may cause irritation of the mucous membrane of the nose and throat, and lung irritation with respiratory distress and cough. Swelling and inflammation of the respiratory tract is seen in serious cases; with headache, nausea, faintness and anxiety. There may also be wheezing.

CHRONIC HEALTH EFFECTS

- There is limited evidence that, skin contact with this product is more likely to cause a sensitisation reaction in some persons compared to the general population.

TOXICITY AND IRRITATION

- Not available. Refer to individual constituents.

OCTADECYLAMINE:

- unless otherwise specified data extracted from RTECS - Register of Toxic Effects of Chemical Substances.

TOXICITY

IRRITATION

Skin (rabbit): 20 mg/24h Moderate

Eye (rabbit): SEVERE

- Contact allergies quickly manifest themselves as contact eczema, more rarely as urticaria or Quincke's oedema. The pathogenesis of contact eczema involves a cell-mediated (T lymphocytes) immune reaction of the delayed type. Other allergic skin reactions, e.g. contact urticaria, involve antibody-mediated immune reactions. The significance of the contact allergen is not simply determined by its sensitisation potential: the distribution of the substance and the opportunities for contact with it are equally important. A weakly sensitising substance which is widely distributed can be a more important allergen than one with stronger sensitising potential with which few individuals come into contact. From a clinical point of view, substances are noteworthy if they produce an allergic test reaction in more than 1% of the persons tested.

Asthma-like symptoms may continue for months or even years after exposure to the material ceases. This may be due to a non-allergenic condition known as reactive airways dysfunction syndrome (RADS) which can occur following exposure to high levels of highly irritating compound. Key criteria for the diagnosis of RADS include the absence of preceding respiratory disease, in a non-atopic individual, with abrupt onset of persistent asthma-like symptoms within minutes to hours of a documented exposure to the irritant. A reversible airflow pattern, on spirometry, with the presence of moderate to severe bronchial hyperreactivity on methacholine challenge testing and the lack of minimal lymphocytic inflammation, without eosinophilia, have also been included in the criteria for diagnosis of RADS. RADS (or asthma) following an irritating inhalation is an infrequent disorder with rates related to the concentration of and duration of exposure to the irritating substance. Industrial bronchitis, on the other hand, is a disorder that occurs as result of exposure due to high concentrations of irritating substance (often particulate in nature) and is completely reversible after exposure ceases. The disorder is characterised by dyspnea, cough and mucus production.

For Fatty Nitrogen-Derived ether amines and Fatty Nitrogen-derived amines (FND ether amines and FND amines):

FND ether amines and FND amines are very similar in structure and function. The minimal difference among the alkyl substituents and the large database for the FND categories indicates that the structural differences in these large alkyl chains do not result in differences in toxicity or mutagenicity.

The differences in chain length, degree of saturation of the carbon chains, source of the natural oils, or addition of an amino group in the chain would not be expected to have an impact on the toxicity profile. This conclusion is supported by a number of studies in the FND family of chemicals (amines, cationics, and amides as separate categories) that show no differences in the length or degree of saturation of the alkyl substituents and is also supported by the limited toxicity of these long-chain substituted chemicals

The available acute oral LD50 study for the propanamine derivative with the extensive data for the other supporting chemicals provides adequate evidence that the FND ether amines are only moderately to slightly toxic via this route and exposure period. Acute dermal studies for the supporting chemicals indicate these chemicals can be classified as minimally toxic. Acute inhalation studies did not result in deaths under normal exposure conditions for two chemicals. Repeated dose toxicity studies had similar NOAELs (12.5 to 50 mg/kg/day for rats and 3 or 13 mg/kg/day for dogs). Importantly because the highest exposure potential for some of the FND ether amines is via skin contact, a number of repeat dose dermal studies indicate the chemicals are highly irritating.

No clear organ-specific toxicity occurred in any of the repeat dose studies with the supporting chemicals in the FND ether amines category. In addition, available data indicate that the FND ether amines are unlikely to be mutagenic and that they are not reproductive or developmental toxins

In evaluating potential toxicity of the FND Amines chemicals, it is also useful to review the available data for the related FND Cationic and FND Amides Category chemicals. Acute oral toxicity studies (approximately 80 studies for 40 chemicals in the three categories) provide LD50 values from approximately 400 to 10,000 mg/kg with no apparent organ specific toxicity. Similarly, repeated dose toxicity studies (approximately 35 studies for 15 chemicals) provide NOAELs between 10 and 100 mg/kg/day for rats and slightly lower for dogs. More than 60 genetic toxicity studies (in vitro bacterial and mammalian cells as well as in vivo studies) indicated no mutagenic activity among more than 30 chemicals tested. For reproductive evaluations, 14 studies evaluated reproductive endpoints and/or reproductive organs for 11 chemicals, and 15 studies evaluated developmental toxicity for 13 chemicals indicating no reproductive or developmental effects for the FND group as a whole.

The material may cause skin irritation after prolonged or repeated exposure and may produce on contact skin redness, swelling, the production of vesicles, scaling and thickening of the skin.

WATER:

SPIRAX SARCO SIGMA 9Hazard Alert Code:
HIGH

Chemwatch Material Safety Data Sheet

Revision No: 3

Chemwatch 4925-46

Issue Date: 29-Jan-2010

CD 2010/1

- No significant acute toxicological data identified in literature search.

Section 12 - ECOLOGICAL INFORMATION

Refer to data for ingredients, which follows:

SPIRAX SARCO SIGMA 9:

OCTADECYLAMINE:

- Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
- Do NOT allow product to come in contact with surface waters or to intertidal areas below the mean high water mark. Do not contaminate water when cleaning equipment or disposing of equipment wash-waters.

Wastes resulting from use of the product must be disposed of on site or at approved waste sites.

- For Fatty Nitrogen-derived ether amines and Fatty Nitrogen-Derived amines (FND ether amines and FND amines):

Environmental fate:

Consistent with the size and nature of these molecules, measured and modeled vapor pressures are very low, and the FND ether amines are considered to be essentially nonvolatile. Measurement and prediction of physical/chemical properties for surfactants are complicated by their behavior in test systems and the environment, and the log Kow is not an appropriate hydrophobicity parameter for reliably predicting environmental behavior. Prediction of physical/chemical properties, including strong adsorption and absorption properties (log Koc) and surface tension activity is unreliable for the same reasons.

Water solubility estimates varied from slightly soluble to very insoluble.

Fugacity models predict virtually no occurrence of the FND ether amines in air, which is consistent with the very low vapor pressures. Nonetheless, modeling indicates that they would be expected to degrade relatively rapidly upon exposure to light (t1/2 values ranging from approximately 1.0 to 2.8 hours).

Distribution to air and soil were < 1% for all of the chemicals that could be modeled while distribution to the water compartment varied from 5 to 90% with the remainder in the sediment.

Overall, FND ether amines have been shown to be either readily biodegradable or to attain degradation close to meeting the "readily biodegradable" criteria.

Ecotoxicity:

A number of studies evaluating the toxicity of the structurally related chemicals, to fish, have been reported. Three assays for one such chemical indicated substantial differences in the measured toxicity ranging from 23 to > 1000 mg/L. Again, this range shows the complexity of testing these types of chemicals.

It is likely that the range of values represents bioavailability or physical availability (important because many surfactant-like chemicals are known to kill aquatic organisms via a physical rather than chemical mechanism) of the test chemical to the fish. Except where bioavailability questions arose, reported LC50 values ranged from 0.11 to 9.3 mg/L. These findings are consistent with the FND surfactants (cationics, amides, nitriles, ether nitriles) in general and support the conclusion that the FND chemicals are toxic to fish when bioavailable, presumably due to their surfactant properties.

Similar to the fish testing, a series of studies evaluating toxicity to aquatic invertebrates is available for structurally related chemicals with EC50 values ranging between 0.011 and 21 mg/L, except where bioavailability questions arose. Acute toxicity to daphnia was confounded by solubility problems and yielded higher than expected EC50 values. In addition, a study examining a mixture of an FND active ingredient with inert materials (e.g. as used in soap) and using two water sources, indicated that river water reduced the toxicity compared to well water (EC50 = 60 vs 22 mg/L, respectively) and that the inert ingredients tended to reduce toxicity (EC50 = 6.5 mg/L for the 83.5% material vs 22 mg/L for the 63% material).

Toxicity to aquatic plants for structurally related chemicals indicates that these amine surfactants are highly toxic to algae (EbC50 and ErC50 values ranging from 0.00075 to 0.17 mg/L).

- DO NOT discharge into sewer or waterways.

WATER:

Ecotoxicity

Ingredient	Persistence: Water/Soil	Persistence: Air	Bioaccumulation	Mobility
octadecylamine	LOW		LOW	LOW
water	LOW		LOW	HIGH

Section 13 - DISPOSAL CONSIDERATIONS

- Recycle wherever possible.
- Consult manufacturer for recycling options or consult local or regional waste management authority for disposal if no suitable treatment or disposal facility can be identified.
- Dispose of by: burial in a land-fill specifically licenced to accept chemical and / or pharmaceutical wastes or incineration in a licenced apparatus (after admixture with suitable combustible material).
- Decontaminate empty containers. Observe all label safeguards until containers are cleaned and destroyed.

Section 14 - TRANSPORTATION INFORMATION**HAZCHEM:**

None (ADG7)

NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS: ADG7, UN, IATA, IMDG

Section 15 - REGULATORY INFORMATION**POISONS SCHEDULE**

None

REGULATIONS

Regulations for ingredients

octadecylamine (CAS: 124-30-1) is found on the following regulatory lists;

"Australia Inventory of Chemical Substances (AICS)", "International Council of Chemical Associations (ICCA) - High Production Volume List", "OECD Representative List of High Production Volume (HPV) Chemicals"

water (CAS: 7732-18-5) is found on the following regulatory lists;

SPIRAX SARCO SIGMA 9

Hazard Alert Code:
HIGH

Chemwatch Material Safety Data Sheet

Revision No: 3

Chemwatch 4925-46

Issue Date: 29-Jan-2010

CD 2010/1

"Australia Inventory of Chemical Substances (AICS)", "IMO IBC Code Chapter 18: List of products to which the Code does not apply", "OECD Representative List of High Production Volume (HPV) Chemicals"

No data for Spirax Sarco Sigma 9 (CW: 4925-46)

Section 16 - OTHER INFORMATION

Denmark Advisory list for selfclassification of dangerous substances

Substance CAS Suggested codes octadecylamine 124- 30- 1 N R50/53

EXPOSURE STANDARD FOR MIXTURES

■ "Worst Case" computer-aided prediction of spray/ mist or fume/ dust components and concentration: ■ Composite Exposure Standard for Mixture (TWA) :100 mg/m³.

■ Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

A list of reference resources used to assist the committee may be found at:

www.chemwatch.net/references.

■ The (M)SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

This document is copyright. Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH. TEL (+61 3) 9572 4700.

Issue Date: 29-Jan-2010

Print Date:13-Jul-2010