

SERVIVAP MK3106**Hazard Alert Code:
MODERATE**

Chemwatch Material Safety Data Sheet

Revision No: 2.0

Chemwatch 16-4545

Issue Date: 8-Sep-2008

CD 2010/1

Section 1 - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION**PRODUCT NAME**

SERVIVAP MK3106

PRODUCT USE

- Used according to manufacturer's directions. High performance corrosion and scale inhibitor for all steam systems.

SUPPLIER

Company: Spirax Sarco Pty Ltd

Address:

72 Mica Street

Carole Park

QLD, 4300






AUS

Telephone: +61 7 3879 4944

Telephone: +61 414 355 619 A/H

Fax: +61 7 3271 4589

Section 2 - HAZARDS IDENTIFICATION**STATEMENT OF HAZARDOUS NATURE****NON-HAZARDOUS SUBSTANCE. NON-DANGEROUS GOODS. According to NOHSC Criteria, and ADG Code.****HAZARD RATINGS**

	Min	Max	
Flammability:	0		
Toxicity:	2		
Body Contact:	2		
Reactivity:	0		Min/Nil=0 Low=1 Moderate=2 High=3 Extreme=4
Chronic:	2		

POISONS SCHEDULE

None

RISK

- Ingestion may produce health damage*.
- Cumulative effects may result following exposure*.
- May produce discomfort of the eyes and skin*.
- Limited evidence of a carcinogenic effect*.
- Possible respiratory and skin sensitiser*.
- Repeated exposure potentially causes skin dryness and cracking*.

* (limited evidence).

SAFETY

- Do not breathe gas/ fumes/ vapour/ spray.
- Avoid contact with skin.
- Wear eye/ face protection.
- In case of contact with eyes rinse with plenty of water and contact Doctor or Poisons Information Centre.

Section 3 - COMPOSITION / INFORMATION ON INGREDIENTS

NAME	CAS RN	%
nonhazardous ingredients		100

Section 4 - FIRST AID MEASURES**SWALLOWED**

- If swallowed do NOT induce vomiting.
- If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration.
- Observe the patient carefully.
- Never give liquid to a person showing signs of being sleepy or with reduced awareness; i.e. becoming unconscious.
- Give water to rinse out mouth, then provide liquid slowly and as much as casualty can comfortably drink.
- Seek medical advice.

EYE

- If this product comes in contact with the eyes:
 - Wash out immediately with fresh running water.

SERVIVAP MK3106**Hazard Alert Code:
MODERATE**

Chemwatch Material Safety Data Sheet

Revision No: 2.0

Chemwatch 16-4545

Issue Date: 8-Sep-2008

CD 2010/1

- Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids.
- Seek medical attention without delay; if pain persists or recurs seek medical attention.
- Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.

SKIN

- If skin contact occurs:
 - Immediately remove all contaminated clothing, including footwear.
 - Flush skin and hair with running water (and soap if available).
 - Seek medical attention in event of irritation.

INHALED

- - If fumes or combustion products are inhaled remove from contaminated area.
 - Other measures are usually unnecessary.

NOTES TO PHYSICIAN

- Treat symptomatically.

for irritant gas exposures:

- the presence of the agent when it is inhaled is evanescent (of short duration) and therefore, cannot be washed away or otherwise removed
- arterial blood gases are of primary importance to aid in determination of the extent of damage. Never discharge a patient significantly exposed to an irritant gas without obtaining an arterial blood sample.
- supportive measures include suctioning (intubation may be required), volume cycle ventilator support (positive and expiratory pressure (PEEP), steroids and antibiotics, after a culture is taken
- If the eyes are involved, an ophthalmologic consultation is recommended

Occupational Medicine: Third Edition ; Zenz, Dickerson, Horvath 1994 Pub: Mosby.

For acute or short term repeated exposures to ammonia and its solutions:

- Mild to moderate inhalation exposures produce headache, cough, bronchospasm, nausea, vomiting, pharyngeal and retrosternal pain and conjunctivitis. Severe inhalation produces laryngospasm, signs of upper airway obstruction (stridor, hoarseness, difficulty in speaking) and, in excessively, high doses, pulmonary oedema.
- Warm humidified air may soothe bronchial irritation.
- Test all patients with conjunctival irritation for corneal abrasion (fluorescein stain, slit lamp exam)
- Dyspneic patients should receive a chest X-ray and arterial blood gases to detect pulmonary oedema.

Section 5 - FIRE FIGHTING MEASURES**EXTINGUISHING MEDIA**

■ The product contains a substantial proportion of water, therefore there are no restrictions on the type of extinguishing media which may be used. Choice of extinguishing media should take into account surrounding areas. Though the material is non-combustible, evaporation of water from the mixture, caused by the heat of nearby fire, may produce floating layers of combustible substances.

In such an event consider:

- foam.
- dry chemical powder.
- carbon dioxide.

FIRE FIGHTING

- - Alert Fire Brigade and tell them location and nature of hazard.
 - Wear breathing apparatus plus protective gloves for fire only.
 - Prevent, by any means available, spillage from entering drains or water courses.
 - Use fire fighting procedures suitable for surrounding area.
 - DO NOT approach containers suspected to be hot.
 - Cool fire exposed containers with water spray from a protected location.
 - If safe to do so, remove containers from path of fire.
 - Equipment should be thoroughly decontaminated after use.

FIRE/EXPLOSION HAZARD

■ The emulsion is not combustible under normal conditions. However, it will break down under fire conditions and the hydrocarbon component will burn.

Decomposes on heating and produces toxic fumes of: carbon dioxide (CO₂), sulfur oxides (SO_x), other pyrolysis products typical of burning organic material.

May emit poisonous fumes.

May emit corrosive fumes.

FIRE INCOMPATIBILITY

- None known.

HAZCHEM

None

PERSONAL PROTECTION

Glasses:	Gloves:	Respirator:
Chemical goggles.	PVC chemical resistant type.	Type K-P Filter of sufficient capacity

Section 6 - ACCIDENTAL RELEASE MEASURES**EMERGENCY PROCEDURES****MINOR SPILLS**

- - Clean up all spills immediately.
 - Avoid breathing vapours and contact with skin and eyes.

SERVIVAP MK3106**Hazard Alert Code:
MODERATE**

Chemwatch Material Safety Data Sheet

Revision No: 2.0

Chemwatch 16-4545

Issue Date: 8-Sep-2008

CD 2010/1

- Control personal contact by using protective equipment.
- Contain and absorb spill with sand, earth, inert material or vermiculite.
- Wipe up.
- Place in a suitable, labelled container for waste disposal.

MAJOR SPILLS

- Moderate hazard.
 - Clear area of personnel and move upwind.
 - Alert Fire Brigade and tell them location and nature of hazard.
 - Wear breathing apparatus plus protective gloves.
 - Prevent, by any means available, spillage from entering drains or water course.
 - Stop leak if safe to do so.
 - Contain spill with sand, earth or vermiculite.
 - Collect recoverable product into labelled containers for recycling.
 - Neutralise/decontaminate residue.
 - Collect solid residues and seal in labelled drums for disposal.
 - Wash area and prevent runoff into drains.
 - After clean up operations, decontaminate and launder all protective clothing and equipment before storing and re-using.
 - If contamination of drains or waterways occurs, advise emergency services.

Personal Protective Equipment advice is contained in Section 8 of the MSDS.

Section 7 - HANDLING AND STORAGE**PROCEDURE FOR HANDLING**

- - DO NOT allow clothing wet with material to stay in contact with skin
 - Avoid all personal contact, including inhalation.
 - Wear protective clothing when risk of exposure occurs.
 - Use in a well-ventilated area.
 - Prevent concentration in hollows and sumps.
 - DO NOT enter confined spaces until atmosphere has been checked.
 - DO NOT allow material to contact humans, exposed food or food utensils.
 - Avoid contact with incompatible materials.
 - When handling, DO NOT eat, drink or smoke.
 - Keep containers securely sealed when not in use.
 - Avoid physical damage to containers.
 - Always wash hands with soap and water after handling.
 - Work clothes should be laundered separately. Launder contaminated clothing before re-use.
 - Use good occupational work practice.
 - Observe manufacturer's storing and handling recommendations.
 - Atmosphere should be regularly checked against established exposure standards to ensure safe working conditions are maintained.

SUITABLE CONTAINER

- - Polyethylene or polypropylene container.
 - Packing as recommended by manufacturer.
 - Check all containers are clearly labelled and free from leaks.

STORAGE INCOMPATIBILITY

- None known.

STORAGE REQUIREMENTS

- - Store in original containers.
 - Keep containers securely sealed.
 - Store in a cool, dry, well-ventilated area.
 - Store away from incompatible materials and foodstuff containers.
 - Protect containers against physical damage and check regularly for leaks.
 - Observe manufacturer's storing and handling recommendations.

SAFE STORAGE WITH OTHER CLASSIFIED CHEMICALS

+: May be stored together
 O: May be stored together with specific precautions
 X: Must not be stored together

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION**EXPOSURE CONTROLS**

SERVIVAP MK3106

**Hazard Alert Code:
MODERATE**

Chemwatch Material Safety Data Sheet

Revision No: 2.0

Chemwatch 16-4545

Issue Date: 8-Sep-2008

CD 2010/1

MATERIAL DATA

SERVIVAP MK3106:

■ for exposure to ammonia gas/ vapours:

Odour Threshold Value: Variously reported as 0.019 ppm and 55 ppm; AIHA Value 16.7 ppm (detection)

NOTE: Detector tubes for ammonia, measuring in excess of 1 ppm, are commercially available.

The TLV-TWA is thought to be protective against irritation of the eyes and respiratory tract and minimise discomfort among workers that are not inured to its effects and systemic damage. Acclimatised persons are able to tolerate prolonged exposures of up to 100 ppm without symptoms. Marked irritation has been seen in persons exposed to ammonia concentrations between 50 and 100 ppm only when the exposures involved sudden concentration peaks which do not permit short-term acclimatisation. The detoxification capacity of the liver is significant since the amount of ammonia formed endogenously in the intestines markedly exceeds that from external sources.

Human exposure effects, at vapour concentrations of about:

Concentration (ppm)	Possible Effects
5	minimal irritation
9-50	nasal dryness, olfactory fatigue and moderate irritation
125-137	definite nose, throat and chest irritation
140	slight eye irritation
150	laryngeal spasm
500	30 minute exposures may produce cyclic hypernea, increased blood pressure and pulse rate, and upper respiratory tract irritation which may persist for 24 hours
700	immediate eye irritation
1,500-10,000	dyspnea, convulsive coughing, chest pain, respiratory spasm, pink frothy sputum, rapid asphyxia and delayed pulmonary oedema which may be fatal. Other effects include runny nose, swelling of the lips, restlessness, headache, salivation, nausea, vomiting, glottal oedema, pharyngitis, tracheitis, and speech difficulties. Bronchopneumonia, asphyxiation due to spasms, inflammation, and oedema of the larynx, may be fatal. Residual effects include hoarseness, productive cough, and decreased respiratory function

>2,500 severe eye irritation, with swelling of the eyelids, lachrymation, blepharospasm, palpebral oedema, increased intraocular pressure, oval semi-dilated, fixed pupils, corneal ulceration (often severe) and temporary blindness. Depending on duration of exposure, there may be destruction of the epithelium, corneal and lenticular opacification, and iritis accompanied by hypopyon or haemorrhage and possible loss of pigment from the posterior layer of the iris. Less severe damage is often resolved. In the case of severe damage, symptoms may be delayed; late complications including persistent oedema, vascularisation and corneal scarring, permanent opacity, acute angle glaucoma, staphyloma, cataract, and atrophy of the retina, iris, and symblepharon. Long-term exposure to sub-acute concentrations or single exposures to high concentrations may produce chronic airway dysfunction, alveolar disease, bronchiolitis, bronchiectasis, emphysema and anxiety neuroses

Odour Safety Factor(OSF)

OSF=3.8 (AMMONIA).

PERSONAL PROTECTION



EYE

-
- Safety glasses with side shields.
- Chemical goggles.
- Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lens or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in their removal and suitable equipment should be readily available. In the event of chemical exposure, begin eye irrigation immediately and remove contact lens as soon as practicable. Lens should be removed at the first signs of eye redness or irritation - lens should be removed in a clean environment only after workers have washed hands thoroughly. [CDC NIOSH Current Intelligence Bulletin 59]

HANDS/FEET

-
- Wear chemical protective gloves, eg. PVC.
- Wear safety footwear or safety gumboots, eg. Rubber

NOTE:

- The material may produce skin sensitisation in predisposed individuals. Care must be taken, when removing gloves and other protective equipment, to avoid all possible skin contact.

- Contaminated leather items, such as shoes, belts and watch-bands should be removed and destroyed.

Suitability and durability of glove type is dependent on usage. Important factors in the selection of gloves include: such as:

- frequency and duration of contact,
- chemical resistance of glove material,
- glove thickness and
- dexterity

Select gloves tested to a relevant standard (e.g. Europe EN 374, US F739).

- When prolonged or frequently repeated contact may occur, a glove with a protection class of 5 or higher (breakthrough time greater than 240 minutes according to EN 374) is recommended.
- When only brief contact is expected, a glove with a protection class of 3 or higher (breakthrough time greater than 60 minutes according to EN 374) is recommended.
- Contaminated gloves should be replaced.

Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed

SERVIVAP MK3106**Hazard Alert Code:
MODERATE**

Chemwatch Material Safety Data Sheet

Revision No: 2.0

Chemwatch 16-4545

Issue Date: 8-Sep-2008

CD 2010/1

moisturiser is recommended.

OTHER

■

- Overalls.
- P.V.C. apron.
- Barrier cream.
- Skin cleansing cream.
- Eye wash unit.

RESPIRATOR

■ Selection of the Class and Type of respirator will depend upon the level of breathing zone contaminant and the chemical nature of the contaminant. Protection Factors (defined as the ratio of contaminant outside and inside the mask) may also be important.

Breathing Zone Level ppm (volume)	Maximum Protection Factor	Half-face Respirator	Full-Face Respirator
1000	10	K-AUS P	-
1000	50	-	K-AUS P
5000	50	Airline *	-
5000	100	-	K-2 P
10000	100	-	K-3 P
	100+		Airline**

* - Continuous Flow ** - Continuous-flow or positive pressure demand.

The local concentration of material, quantity and conditions of use determine the type of personal protective equipment required. For further information consult site specific CHEMWATCH data (if available), or your Occupational Health and Safety Advisor.

ENGINEERING CONTROLS

■ General exhaust is adequate under normal operating conditions. Local exhaust ventilation may be required in specific circumstances. If risk of overexposure exists, wear approved respirator. Correct fit is essential to obtain adequate protection. Provide adequate ventilation in warehouse or closed storage areas. Air contaminants generated in the workplace possess varying "escape" velocities which, in turn, determine the "capture velocities" of fresh circulating air required to effectively remove the contaminant.

Type of Contaminant:	Air Speed:
solvent, vapours, degreasing etc., evaporating from tank (in still air).	0.25-0.5 m/s (50-100 f/min)
aerosols, fumes from pouring operations, intermittent container filling, low speed conveyer transfers, welding, spray drift, plating acid fumes, pickling (released at low velocity into zone of active generation)	0.5-1 m/s (100-200 f/min.)
direct spray, spray painting in shallow booths, drum filling, conveyer loading, crusher dusts, gas discharge (active generation into zone of rapid air motion)	1-2.5 m/s (200-500 f/min.)
grinding, abrasive blasting, tumbling, high speed wheel generated dusts (released at high initial velocity into zone of very high rapid air motion).	2.5-10 m/s (500-2000 f/min.)
Within each range the appropriate value depends on:	
Lower end of the range	Upper end of the range
1: Room air currents minimal or favourable to capture	1: Disturbing room air currents
2: Contaminants of low toxicity or of nuisance value only.	2: Contaminants of high toxicity
3: Intermittent, low production.	3: High production, heavy use
4: Large hood or large air mass in motion	4: Small hood-local control only

Simple theory shows that air velocity falls rapidly with distance away from the opening of a simple extraction pipe. Velocity generally decreases with the square of distance from the extraction point (in simple cases). Therefore the air speed at the extraction point should be adjusted, accordingly, after reference to distance from the contaminating source. The air velocity at the extraction fan, for example, should be a minimum of 1-2 m/s (200-400 f/min) for extraction of solvents generated in a tank 2 meters distant from the extraction point. Other mechanical considerations, producing performance deficits within the extraction apparatus, make it essential that theoretical air velocities are multiplied by factors of 10 or more when extraction systems are installed or used.

Section 9 - PHYSICAL AND CHEMICAL PROPERTIES**APPEARANCE**

Black liquid with a characteristic odour; mixes with water.

PHYSICAL PROPERTIES

Liquid.
Mixes with water.

State	Liquid	Molecular Weight	Not Applicable
Melting Range (°C)	Not Available	Viscosity	Not Available
Boiling Range (°C)	Not Available	Solubility in water (g/L)	Miscible
Flash Point (°C)	Not Available	pH (1% solution)	Not Available
Decomposition Temp (°C)	Not Available	pH (as supplied)	Not Available
Autoignition Temp (°C)	Not Available	Vapour Pressure (kPa)	Not Available

SERVIVAP MK3106**Hazard Alert Code:
MODERATE**

Chemwatch Material Safety Data Sheet

Revision No: 2.0

Chemwatch 16-4545

Issue Date: 8-Sep-2008

CD 2010/1

Upper Explosive Limit (%)	Not Available	Specific Gravity (water=1)	1.17
Lower Explosive Limit (%)	Not Available	Relative Vapour Density (air=1)	Not Available
Volatile Component (%vol)	Not Available	Evaporation Rate	Not Available

Section 10 - CHEMICAL STABILITY**CONDITIONS CONTRIBUTING TO INSTABILITY**

-
- Presence of incompatible materials.
- Product is considered stable.
- Hazardous polymerisation will not occur.

For incompatible materials - refer to Section 7 - Handling and Storage.

Section 11 - TOXICOLOGICAL INFORMATION**POTENTIAL HEALTH EFFECTS****ACUTE HEALTH EFFECTS****SWALLOWED**

- Considered an unlikely route of entry in commercial/industrial environments.

Ingestion may result in nausea, abdominal irritation, pain and vomiting.

Ingestion of anionic surfactants may produce diarrhoea, bloated stomach, and occasional vomiting.

EYE

- There is some evidence to suggest that this material can cause eye irritation and damage in some persons.

Direct eye contact with some anionic surfactants in high concentration can cause severe damage to the cornea. Low concentrations can cause discomfort, excess blood flow, and corneal clouding and swelling. Recovery may take several days.

SKIN

- Anionic surfactants can cause skin redness and pain, as well as a rash. Cracking, scaling and blistering can occur.

Open cuts, abraded or irritated skin should not be exposed to this material.

Entry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external damage is suitably protected.

Mild irritation is produced on moist skin when vapour concentrations of ammonia exceed 10000 ppm. High vapour concentrations (>30000 ppm) or direct contact with solutions produces severe pain, a stinging sensation, burns and vesiculation and possible brown stains. Extensive burning may be fatal. Vapour exposure may, rarely, produce urticaria.

INHALED

- Not normally a hazard due to non-volatile nature of product.

CHRONIC HEALTH EFFECTS

- Principal routes of exposure are by accidental skin and eye contact and by inhalation of vapours especially at higher temperatures.

Substance accumulation, in the human body, may occur and may cause some concern following repeated or long-term occupational exposure.

There is limited evidence that, skin contact with this product is more likely to cause a sensitisation reaction in some persons compared to the general population.

TOXICITY AND IRRITATION

- Not available. Refer to individual constituents.

Section 12 - ECOLOGICAL INFORMATION

Refer to data for ingredients, which follows:

SERVIVAP MK3106:

- For surfactants:

Environmental fate:

Octanol/water partition coefficients cannot easily be determined for surfactants because one part of the molecule is hydrophilic and the other part is hydrophobic. Consequently they tend to accumulate at the interface and are not extracted into one or other of the liquid phases. As a result surfactants are expected to transfer slowly, for example, from water into the flesh of fish. During this process, readily biodegradable surfactants are expected to be metabolised rapidly during the process of bioaccumulation. This was emphasised by the OECD Expert Group stating that chemicals are not to be considered to show bioaccumulation potential if they are readily biodegradable.

Several anionic and nonionic surfactants have been investigated to evaluate their potential to bioconcentrate in fish. BCF values (BCF - bioconcentration factor) ranging from 1 to 350 were found. These are absolute maximum values, resulting from the radiolabelling technique used. In all these studies, substantial oxidative metabolism was found resulting in the highest radioactivity in the gall bladder. This indicates liver transformation of the parent compound and biliary excretion of the metabolised compounds, so that "real" bioconcentration is overstated. After correction it can be expected that "real" parent BCF values are one order of magnitude less than those indicated above, i.e. "real" BCF is <100. Therefore the usual data used for classification by EU directives to determine whether a substance is "Dangerous to the Environment" has little bearing on whether the use of the surfactant is environmentally acceptable.

Ecotoxicity:

Surfactant should be considered to be toxic (EC50 and LC50 values of < 10 mg/L) to aquatic species under conditions that allow contact of the chemicals with the organisms. The water solubility of the chemicals does not impact the toxicity except as it relates to the ability to conduct tests appropriately to obtain exposure of the test species. The acute aquatic toxicity generally is considered to be related to the effects of the surfactant properties on the organism and not to direct chemical toxicity.

SERVIVAP MK3106**Hazard Alert Code:
MODERATE**

Chemwatch Material Safety Data Sheet

Revision No: 2.0

Chemwatch 16-4545

Issue Date: 8-Sep-2008

CD 2010/1

■ Extensive studies have been conducted to evaluate the effects of lignosulfonate on the environment. Results show that they are not harmful to plants, animals or aquatic life. Toxic levels of lignosulfonates in surface water have been established and confirm that concentrations must be relatively high before fish and other organisms are affected. Fish LC50s are calculated to be 5200-6400 ppm (practically non-toxic). Vegetation and growth of fir trees were not significantly affected at normal and above normal application rates of lignosulfonates.

There may be concerns associated with increased oxygen demand in waters where lignosulfonates are introduced directly into a stream from pulping plants. Receiving water near pulping plants experiences an increased oxygen demand and the water takes on a yellowish-brown tint. Effluent from pulping plants is often up to 55% lignosulfonates.

The effect of lignosulfonates on bacterial reproduction rate in recirculated cooling water was studied by plate counting method. It was found that both wood-pulp and straw-pulp lignosulfonates hasten bacterial reproduction. Sugar in lignosulfonates was the main factor that hasten bacterial reproduction. However, modified lignosulfonates inhibit bacterial reproduction. Lignosulfonate oxidised by hydrogen peroxide also inhibited bacterial reproduction. It was determined that except under extreme soil pH conditions (<1), the release of sulfur dioxide from the application of lignosulfonates is essentially non-existent. The odour associated with the application of lignosulfonates to roads (as dust suppressant) was found to be due to trace amounts of organic compounds mainly of the furfural variety.

There appears to be little if any research describing movement of lignosulfonates in the soil and whether they can leach into surface or ground water

Lignosulfonate is a complex mixture of small- to moderate-sized polymeric compounds with sulfonate groups attached to the molecule. The product commonly designated "lignosulfonate" is really a mixture of sulfonated lignin, sugars, sugar acids, resins and inorganic chemicals. This complex and variable mixture is water soluble.

Lignosulfonate is a highly anionic polymer used to deflocculate clay-based muds; in addition it is used as a cement additive where it binds to the surface of cement particles and delays absorption of water and this influence hardening rates. Lignosulfonate is a byproduct of the sulfite method for manufacturing paper from wood pulp. Lignosulfonates form colloidal solutions or dispersions with water but are not soluble in organic solvents. Lignosulfonates are biopolymers; they are salts of lignosulfonic acid that has been formed when pulp is manufactured by the sulphite method. The lignosulfonates are of varied composition because the woods are different, the extent of the lignin degradation can be different and a different number of sulfonic groups can have been added. Lignin is a polymer with a most varied length and composition, a fundamental structure being hydroxyphenyl propane. It contains many phenolic rings and methoxy groups.

Lignosulfonate is derived from wood and thus contain trace amounts of the metals that are naturally present in trees. The levels and types of metals vary depending upon the types of trees and the soil on which they were grown. The amounts of metals typically found in lignosulfonate are well below one part per million (ppm).

■ Polyanionic monomers, for example, ethylenediaminetetraacetic acid (EDTA) are of concern only for their toxicity to green algae. Toxicity to algae is moderate and it appears that the mode of toxic action of these polyanionic monomers is overchelation of nutrient elements needed by algae for growth. Polyanionic monomers are assessed similarly to the polycarboxylic acid polymers.

■ In air ammonia is persistent whilst, in water, it biodegrades rapidly to nitrate, producing a high oxygen demand. Ammonia is strongly adsorbed to soil. Ammonia is non-persistent in water (half-life 2 days) and is moderately toxic to fish under normal temperature and pH conditions. Ammonia is harmful to aquatic life at low concentrations but does not concentrate in the food chain.

Drinking Water Standards:

0.5 mg/l (UK max.)

1.5 mg/l (WHO Levels)

Soil Guidelines: none available.

Air Quality Standards: none available.

■ DO NOT discharge into sewer or waterways.

Section 13 - DISPOSAL CONSIDERATIONS

■ Legislation addressing waste disposal requirements may differ by country, state and/ or territory. Each user must refer to laws operating in their area. In some areas, certain wastes must be tracked.

A Hierarchy of Controls seems to be common - the user should investigate:

- Reduction
- Reuse
- Recycling
- Disposal (if all else fails)

This material may be recycled if unused, or if it has not been contaminated so as to make it unsuitable for its intended use. If it has been contaminated, it may be possible to reclaim the product by filtration, distillation or some other means. Shelf life considerations should also be applied in making decisions of this type. Note that properties of a material may change in use, and recycling or reuse may not always be appropriate.

- DO NOT allow wash water from cleaning or process equipment to enter drains.
- It may be necessary to collect all wash water for treatment before disposal.
- In all cases disposal to sewer may be subject to local laws and regulations and these should be considered first.
- Where in doubt contact the responsible authority.
- Recycle wherever possible.
- Consult manufacturer for recycling options or consult local or regional waste management authority for disposal if no suitable treatment or disposal facility can be identified.
- Dispose of by: burial in a land-fill specifically licenced to accept chemical and / or pharmaceutical wastes or incineration in a licenced apparatus (after admixture with suitable combustible material).
- Decontaminate empty containers. Observe all label safeguards until containers are cleaned and destroyed.

Section 14 - TRANSPORTATION INFORMATION**HAZCHEM:**

None (ADG7)

NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS: ADG7, UN, IATA, IMDG

Section 15 - REGULATORY INFORMATION**POISONS SCHEDULE**

None

REGULATIONS

No data for SERVIVAP MK3106 (CW: 16-4545)

SERVIVAP MK3106**Hazard Alert Code:
MODERATE**

Chemwatch Material Safety Data Sheet

Revision No: 2.0

Chemwatch 16-4545

Issue Date: 8-Sep-2008

CD 2010/1

Section 16 - OTHER INFORMATION**EXPOSURE STANDARD FOR MIXTURES**

■ "Worst Case" computer-aided prediction of spray/ mist or fume/ dust components and concentration: ■ Composite Exposure Standard for Mixture (TWA) :100 mg/m³.

■ Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

A list of reference resources used to assist the committee may be found at:
www.chemwatch.net/references.

■ The (M)SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

This document is copyright. Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH. TEL (+61 3) 9572 4700.

Issue Date: 8-Sep-2008

Print Date:6-May-2010